

Send mail

```
function sendmail_1(myaddress, mypassword, sendtoaddress, subject,  
emailbody)
```

```
setpref('Internet','E_mail',myaddress);  
setpref('Internet','SMTP_Server','smtp.gmail.com');  
setpref('Internet','SMTP_Username',myaddress);  
setpref('Internet','SMTP_Password',mypassword);
```

```
props = java.lang.System.getProperties;  
props.setProperty('mail.smtp.auth','true');  
props.setProperty('mail.smtp.socketFactory.class', ...  
                'javax.net.ssl.SSLSocketFactory');  
props.setProperty('mail.smtp.socketFactory.port','465');
```

```
[filename, pathname] = uigetfile;  
if ~ischar(filename)  
    return; % User aborted the file selection  
end  
file = fullfile(pathname, filename);  
[fid, msg] = fopen(file, 'r');  
  
if fid == -1  
    error(msg);  
end  
  
fclose(fid);  
  
sendmail(sendtoaddress,subject,emailbody,file );  
  
end
```

Send mail multiple

```
function sendmail_multi(myaddress, mypassword, sendtoaddress,  
subject, emailbody)
```

```
    setpref('Internet','E_mail',myaddress);  
    setpref('Internet','SMTP_Server','smtp.gmail.com');  
    setpref('Internet','SMTP_Username',myaddress);  
    setpref('Internet','SMTP_Password',mypassword);
```

```
    props = java.lang.System.getProperties;  
    props.setProperty('mail.smtp.auth','true');  
    props.setProperty('mail.smtp.socketFactory.class', ...  
        'javax.net.ssl.SSLSocketFactory');  
    props.setProperty('mail.smtp.socketFactory.port','465');
```

```
    sendmail(sendtoaddress, ...  
        subject, emailbody);
```

```
end
```